BRIGHTWELL

Datasheet



EcoMulti Compact 4+2

EcoMulti is a venturi system that can dilute up to 6 chemicals from one dispenser. Ideal for use with spray bottles, buckets or scrubber dryers, the system is designed with two separate proportioners making it suitable for combining high flow (3 gal/min) and low flow (1 gal/min) applications.



Technical specifications		
Dimensions (inches) (H x W x L)	10.5" x 8.25" x 5.25"	
Weight	3.31 Lbs.	
Branding (cm) (H x W)	Center branding plaque: H 1.5 x W 4 Multi-lingual, color-coded chemical pictograms	
Installation	Working temperature range 39.2° - 149° F Working pressure range 2 - 5 bar Minimum water flow required: High flow = 2.25 gal/min Low flow = 1 gal/min	
Dilution	13 independent dilution ratios High Flow 6:1 - 350:1 Low Flow 2:1 - 128:1	
Material	Cover/Backplate: Glass Bead Polypropylene (GBPP) Pusher: ABS Internal tubing and seals: EPDM	

Accessories	Hanging bracket Secure chemical cabinets (2L/5L) Coloured rings
Approvals	ASSE: Record Number: 1562 WaterMark: Licence No. WMK25899 Specification: ATS5200.101 - 2005
Warranty	2 years

In the box			
EcoMulti Compact unit			
Dispenser key			
Ceramic weight x 6			
Foot filter x 6			
Low flow outlet tube with flood ring (unit dependent)			
High flow 1.5m outlet tube with flood ring (unit dependent)			
Clear PVC chemical suction tube - 6 x 9			
Instruction manual and chemical pictograms			
Drilling template			
Screw pack			
Bottle bracket and clips (unit dependent)			
Bucket hook (unit dependent)			

Part numbers	
Part number	Description
DXC4L2H-WK	EcoMulti Compact, 4 x Low Flow, 2 x High Flow, White Cover, Grey Ring, BrightGap





Shipping method	Quantity of units	Dimensions L x W x H (inches)	Net packed weight (lbs.)
Unit	1	15.35" x 12.25" x 6.75"	6.8 lbs
Case	2	24.75" x 21.25" x 10.75"	15.5 lbs.
Pallet	54	47.25" x 39.5" x 46"	421 lbs.
Euro Pallet	36	47.25" x 31.5" x 46"	298 lbs.

BRIGHTWELL

Brightwell Dispensers Inc. 9858 Britton Street Lenexa, KS 66219

T: (+1) 913-956-4909 E: sales@brightwell-inc.com

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.