

BRIGHTWELL

Datasheet



EcoSink 1 chemical



EcoSink is a chemical dispenser for use with single and multi-compartment sinks in commercial kitchens. It is available with BrightGap and AirGap backflow preventers.

EcoSink 2 button dispenses two chemicals with an option to choose from a single or dual water supply.

Technical specifications

Dimensions (inches) (H x W x L)	1 Chemical: 10.16" x 3.86" x 3.15"
Weight	1 Chemical: 4 lbs.
Branding	Multi-colored chemical labels available
Installation	Working temperature range 39.2° - 179.6° F Working pressure range 2 - 5 bar Minimum water flow required: 2.25 gal/min
Dilution	13 independent dilution ratios 6:1 - 695:1
Material	Cover: Stainless Steel Connector Bracket: Polypropylene Valve Switch Dial: Polypropylene Ball Valve and Inlet Connectors: Brass Proportioner Dilution Seal: EPDM/Viton Venturi Assembly: Polypropylene



Operation	Simple twist and lock on/off application
Accessories	Hanging bracket Secure chemical cabinet (2L/5L)
Approvals	ASSE: Record Number:1562
Warranty	1 year

In the box

EcoSink unit
Ceramic weight(s)
Foot filter(s)
Clear PVC chemical suction tube
High flow 1.5m outlet tube with flood ring
Screw pack
Instruction manual and chemical labels

Part numbers

Part number	Description
DS1HC-S	EcoSink 1 Chemical, Highflow, BrightGap

Shipping info - 1 Chemical

Shipping method	Quantity of units	Dimensions L x W x H (inches)	Net packed weight (lbs.)
Unit	1	12.5" x 10.63" x 6.30"	4 lbs.
Case	8	25.75" x 21.5" x 13.75"	35.28 lbs.
Pallet	160	51.5" x 43.30" x 74.80"	738.5 lbs.



BRIGHTWELL

Brightwell Dispensers Inc.
9858 Britton Street
Lenexa, KS
66219

T: (+1) 913-956-4909
E: sales@brightwell-inc.com

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.

