

# BRIGHTWELL

## Datasheet



### Low-Level Alarm

Used in conjunction with Brightwell suction wands, the Low-Level Chemical Alarm can monitor up to 10 chemicals and provide an audible alarm with visual indicator when a chemical level is low.

Available as a stand-alone module or as an integrated version for direct connection to any BrightLogic unit.



#### Technical specifications

<b>Voltage/Frequency</b>	100-240V AC, 50-60Hz
<b>Current</b>	0.11A (@240V)
<b>Power</b>	30W
<b>Outputs</b>	External alarm output - up to 10A 250VAC switching on the NO contacts
<b>Options</b>	BrightLogic add-on version
<b>Enclosure</b>	Polypropylene, IP44
<b>Accessories</b>	Suction Wands External Alarm module
<b>Approvals</b>	CE
<b>Warranty</b>	2 years

#### In the box (should be an image)

Level Alarm Unit



Mounting Kit

Quickstart Guide

### Part Numbers

<b>WLL</b>	Low-Level Alarm (stand alone)
<b>WLL-ADD</b>	Low-Level Alarm (integrated)



Brightwell Dosing Ltd  
Unit 1, Rich Industrial Estate  
Avis Way, Newhaven  
East Sussex, BN9 0DU

T: +44 (0)1273 513 566  
E: sales@brightwell.co.uk

© 2024 Brightwell Dosing Ltd | Registered in England, Number 00661996.

