# Sprite III DM-700

## The new standard in 3 product dispensing



Hydro Systems' Sprite III leads the way in bringing modern technology together with simplified user interface. At last, an institutional chemical dispensing system with auto voltage sensing that allows either 115 or 220 volts to be connected to the single power input leads. Combine this with long-life, spring loaded peristaltic pumps, a new Quik-Klip mounting bracket and simplified three button programming and you have the most innovative chemical feed system on the market.

- Splashproof enclosure
- Easy access, spring-loaded pumps
- Simple, three button programming
- Factory pre-wired
- Auto voltage sensing (no transformers)

# SpriteIII DM-700 System Advantages

## Auto-Voltage Sensing Power Supply
The Sprite III allows either 115 or 220 VAC to be connected to the two power input leads. The Sprite III senses the power you have connected to it and makes all the necessary adjustments automatically.

## Safe Design
For safety and convenience the Sprite III is shipped pre-wired from the factory, making it unnecessary to open the enclosure during installation. A main power and supply signal cable is provided so that technicians need only to make connections at the machine.

## Quick Change Pump Tubes
The Sprite III's peristaltic pump covers are held in place by a single, finger tightened thumb screw. This eliminates the need to use tools when changing the pump tubes. The thumb screws are "captive" in the cover which prevents them from being dropped or lost.

## Quik-Klip Mounting Bracket
Installation of the **Sprite III** is greatly simplified with the help of the new Quik-Klip mounting bracket. A strong, "wedge shaped" bracket with built-in level indicator is included with every **Sprite III**. Attach the bracket to the wall with a single screw and then adjust it left or right until the leveling ball indicates the bracket is square. Set the remaining two screws and then simply lock the dispenser down over the wedge. It couldn't be easier.

## Security
None of the **Sprite III**'s programming functions can be accessed without first entering a three digit security passcode. This prevents unauthorized individuals from tampering with the programs.

| Model | Description |
|---|---|
| DM-711 | Sprite III Warewashing w/ 1 Solenoid & 1 Pump |
| DM-711 w/super kit | Sprite III Warewashing w/ 1 Solenoid & 1 Pump plus Super Kit |
| DM-720 | Sprite III Warewashing w/ 2 Pumps |
| DM-720 w/super kit | Sprite III Warewashing w/ 2 Pumps plus Super Kit |
| DM-721 | Sprite III Warewashing w/ 1 Solenoid & 2 Pumps |
| DM-721 w/super kit | Sprite III Warewashing w/ 1 Solenoid & 2 Pumps plus Super Kit |
| DM-730 | Sprite III Warewashing w/ 3 Pumps |
| DM-730 w/super kit | Sprite III Warewashing w/ 3 Pumps plus Super Kit |

**Hydro** systems
A DOVER COMPANY

**Hydro Systems**
3798 Round Bottom Road
Cincinnati, OH 45244

**Phone**  513.271.8800
**Toll Free**  800.543.7184
**Fax**  513.271.0160
**Web**  hydrosystemsco.com