

# OPL BASIC SERIES DOSING SYSTEMS

OplBasic | L · D · LL · DD · DL



## DESCRIPTION

OPL Basic Series offers a wide range of single and/or two product timed systems for liquid and dry product applications. Chemical dosing is activated automatically by a signal from the washer or by manually pressing the keys located on the front of the unit. (Optional remote manual switch also available).

## OPL BASIC SERIES DOSING SYSTEMS:

- OplBasic L** - system with a peristaltic pump
- OplBasic D** - system with a solenoid valve
- OplBasic LL** - system with double peristaltic pumps
- OplBasic DD** - system with double solenoid valves
- OplBasic DL** - system with peristaltic pump and solenoid valve

## FEATURES

- Dip switches, trimmers and jumpers make calibration and programming quick and easy
- Front cover opens to 90° degrees for easy access to connections
- Easy installation - simply run the tubing and connect to the power supply
- Easily mount and remove with built in mounting brackets. No special tools required
- Safe systems: all settings are made inside the cabinet to discourage tampering
- LED and buzzer signal on empty product warning
- SekoFlex and SekoBril squeeze tubing, equipped with inlet-outlet fittings for fast and safe connections
- Dosing time - accepts program run time 0 - 10 minutes
- Delay time using an internal trimmer, delay the start of the pump from 0 - 5 minutes
- Lock out time prevents repeat dispensing of product from 0 to 75 minutes with dip switch settings



OplBasic L



OplBasic D



OplBasic LL



OplBasic DD



OplBasic DL

# OPL BASIC SERIES DOSING SYSTEMS

OplBasic | L · D · LL · DD · DL



## TECHNICAL SPECIFICATIONS

SPECIFICATION	OplBasic L	OplBasic D	OplBasic LL	OplBasic DD	OplBasic DL
Power supply	115 / 208 / 230 Vac @ 50/60 Hz				
Power consumption	4.5 W	4.5 W	9 W	9 W	9 W
Max flow rate	10 oz/min	-	10 oz/min	-	10 oz/min
Squeeze tube	SekoBril	-	SekoBril	-	SekoBril
Solenoid Valves	-	24 Vdc	-	24 Vdc	24 Vdc
Class of protection	IP 65				

## DIMENSIONS

SYSTEM TYPE	System dimensions (L x H x D)
OplBasic L	195 x 168 x 110 mm (7.7" x 6.6" x 4.3")
OplBasic D	272 x 168 x 78 mm (10.7" x 6.6" x 3.1")
OplBasic LL	195 x 168 x 110 mm (7.7" x 6.6" x 4.3")
OplBasic DD	348 x 168 x 78 mm (13.7" x 6.6" x 3.1")
OplBasic DL	272 x 168 x 110 mm (10.7" x 6.6" x 4.3")