

OPL SERIES DOSING SYSTEM

OPL MINI L



DESCRIPTION

Fixed speed peristaltic pump with digital adjustment of delay, dosing and lock-out time. Suitable for wash wheels up to 50 pounds.

Comes equipped with 2 cables:

- cable 1 for the 100÷240 Vac power supply
- cable 2 dedicated to receiving a 20÷240 Vac signal that activates the dosing cycle.



FEATURES

- **Precise programming** of delay, dosing and lock out times by keys display and microprocessor technology
- **Long lifetime** of **squeeze tube** and motor due to latest Transaxle and Tubing technology
- **NEMA 4X (IP 65)** enclosure for optimum water resistance. SEKO's material and construction offers excellent resistance to impact and chemical exposure
- **Electrical class 2**, no ground wire needed

TECHNICAL SPECIFICATIONS

Power supply	100 ÷ 240 Vac @ 50/60 Hz
Power consumption	5 W
Squeeze tube	SekoFlex
Pressure	max 1.5 psi
Flow rate	8 oz/min
Delay time	from 0 to 999 sec
Lock-out time	from 0 to 999 sec
Class of protection	IP 65 Nema 4X
Dimensions (L x H x D)	127 x 102 x 113 mm (5" x 4" x 4.4")